



XF-PTL04535-F-VI

Specification

Optical structure	Bi-Telecentric
Magnification	0.805
Object field of view	Φ43.5mm
Image field of view	Φ35mm
Working Distance	120mm±3%
Telecentricity	<0.03°(0.07°)
Depth of field	1.3-8.0mm
F#	F7.5-F46.7
Resolution	6.2-38.32μm
MTF	>0.3@140-22lp/mm
Distortion	<0.041%(0.065%)
Detector type:	

2'	23×23	28.6×28.6mm
4/3'	18×13.5	22.4×16.8mm
1.1'	14.2×10.4	17.6×12.9mm
1'	12.8×9.6	15.9×11.9mm
2K Linear scan	2048×10μm	25.4mm
4K Linear scan	4096×7μm	35.6mm

Optional camera mount:
1、F
2、M42×1

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p>	<p>90° Steering option</p>
--	---	-----------------------------------

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL04535-F-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.