



XF-PTL08029-F-VI

Optional camera mount
 1、 F
 2、 M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.363
Object field of view	Φ79.9mm
Image field of view	Φ29.0mm
Working Distance	180mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	5.8-31.6mm
F#	F7-F37.5
Resolution	12.7-68.1μm
MTF	>0.3@145-27lp/mm
Distortion	<0.039%(0.089%)
Detector type:	

7/4'	22.5×16.9	62.0×46.6mm
4/3'	18.0×13.5	49.6×37.2mm
1.1'	14.2×10.4	39.1×28.7mm
1'	12.8×9.6	35.3×26.4mm
2K Linear scan	2048×10μm	56.4mm
4K Linear scan	4096×7μm	79.0mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL08029-F-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.